

# Wrangler® DuraTrac™

A Hardworking, Versatile Tire Offering On- And Off-Road Traction

## Features



## Features

## Benefits

- 1 TractionGroove Technology — Offers enhanced traction in deep mud and snow
- 2 Self-cleaning shoulder blocks — Help provide enhanced dirt, gravel and mud traction
- 3 Highly angled center tread blocks — Help provide enhanced traction and lateral stability while reducing road noise
- 4 Rim protector — Helps protect wheels from accidental curb damage
- 5 Pinned for #16 metal studs\* — Enhanced traction in winter driving conditions

## Performance Ratings

Dry Traction	8
Wet Traction	8
Snow Traction	10
Off-Road Traction	9
Ride Comfort	6
Quiet Ride	6

## Post-Purchase Programs:

- Nationwide Warranty Service
- Online Tire Registration
- See page 2 for complete details.



Mountain Snowflake Designation For Outstanding Winter Traction

## SPECIFICATIONS

SIZE	LI/SS	SIDEWALL	LOAD RANGE	PRODUCT CODE	MATERIAL NUMBER	APPROVED RIM WIDTH (INS)	MEASURING RIM WIDTH (INS)	SECTION WIDTH (INS)	OVERALL DIAMETER (INS)	MAX LOAD @ INFL PRESSURE (LBS @ PSI)	TREAD DEPTH (IN 32NDS)	REVS/ MILE
31X10.50R15LT	109	OWL	C	312007027	208386	7.0 - 9.0	8.5	10.5	30.8	2,270 @ 50	18	676
33X12.50R15LT	108	OWL	C	312020027	208399	8.5 - 11.0	10.0	12.5	32.8	2,205 @ 35	18	635
LT235/75R15	104/101	OWL	C	312008027	208387	6.0 - 7.0	6.5	9.3	29.1	1,985 @ 50	18	715
LT225/75R16	115/112	BSL	E	312009142	208388	6.0 - 7.0	6.0	8.8	29.5	2,680 @ 80	18	704
LT245/75R16	120/116	OWL	E	312249027	208316	6.5 - 8.0	7.0	9.8	30.7	3,042 @ 80	18	677
LT245/75R16	108/104	OWL	C	312017027	208396	6.5 - 8.0	7.0	9.8	30.7	2,205 @ 50	18	677
LT265/75R16	112/109	OWL	C	312018027	208414	7.0 - 8.0	7.5	10.5	31.9	2,470 @ 50	18	652
LT265/75R16	123/120	OWL	E	312004027	208384	7.0 - 8.0	7.5	10.5	31.9	3,415 @ 80	18	652
LT285/75R16	126/123	OWL	E	312005027	208385	7.5 - 9.0	8.0	11.3	33.1	3,750 @ 80	18	629
LT315/75R16	127/124	BSL	E	312013142	208392	8.0 - 10.0	8.5	12.3	34.8	3,860 @ 65	18	598
LT215/85R16	115/112	BSL	E	312010142	208389	5.5 - 7.0	6.0	8.5	30.6	2,680 @ 80	18	679
LT235/85R16	120/116	BSL	E	312021142	208400	6.0 - 7.5	6.5	9.3	32.0	3,042 @ 80	18	651
LT245/70R17	119/116	BSL	E	312022142	208401	6.5 - 8.0	7.0	9.8	30.8	3,000 @ 80	18	676
LT265/70R17	121/118	BSL	E	312014142	208393	7.0 - 8.5	8.0	10.7	31.9	3,195 @ 80	18	652
LT265/70R17	112/109	OWL	C	312019027	208398	7.0 - 8.5	8.0	10.7	31.9	2,470 @ 50	18	652
LT285/70R17	121/118	OWL	D	312015027	208394	7.5 - 9.0	8.5	11.5	33.0	3,195 @ 65	18	630
LT315/70R17	121/118	BSL	D	312031142	208413	8.5 - 10.0	9.5	12.7	34.7	3,195 @ 50	18	600
LT245/75R17	121/118	OWL	E	312023027	208347	6.5 - 7.5	7.0	9.8	31.7	3,195 @ 80	18	656
LT275/65R18	123/120	BSL	E	312011142	208390	7.5 - 9.0	8.0	11.0	32.3	3,085 @ 80	18	644
LT295/65R18	127/124	BSL	E	312024142	208348	8.0 - 10.0	8.5	11.8	33.4	3,860 @ 80	18	624
LT325/65R18	127/124	BSL	E	312016142	208395	9.0 - 12.0	9.5	13.0	34.8	3,860 @ 65	18	597
LT275/70R18	125/122	BSL	E	312012142	208391	7.0 - 8.5	8.0	11.0	33.4	3,640 @ 80	18	622
LT305/55R20	121/118	BSL	E	312030142	208412	8.5 - 11.0	9.5	12.4	33.5	3,195 @ 65	18	622
LT285/60R20	125/122	BSL	E	312028142	208350	8.0 - 10.0	8.5	11.5	33.5	3,640 @ 80	18	621
LT325/60R20	126	BSL	E	312029142	208411	9.0 - 12.0	9.5	13.0	35.6	3,750 @ 65	18	584
LT275/65R20	126/123	BSL	E	312025142	208349	7.5 - 9.5	8.0	11.0	34.3	3,750 @ 80	18	606

CALL FOR PRICING

## CROSS REFERENCE LARGE OVERALL DIAMETER SIZES

RIM DIAMETER	OVERALL DIAMETER	SECTION WIDTH	SIZE
16	33.1	11.3	LT285/75R16
16	34.8	12.3	LT315/75R16
17	33.0	11.5	LT285/70R17
17	34.7	12.7	LT315/70R17
18	33.4	11.8	LT295/65R18
18	33.4	11.0	LT275/70R18
18	34.8	13.0	LT325/65R18
20	33.5	12.4	LT305/55R20
20	33.5	11.5	LT285/60R20
20	35.6	13.0	LT325/60R20

For more complete information, go to Tire-HQ™ at [www.tire-hq.com](http://www.tire-hq.com).

## ADIRONDACK TIRE

NEW TIRE PURCHASE INCLUDES:

- \* FREE MOUNTING
- \* FREE BALANCING
- \* FREE LIFETIME ROTATION
- \* FREE PUNCTURE REPAIR

\* Consult state and provincial laws regarding stud use. Use stud #16.